

# SUPRESS<sup>BRAND</sup>

## MATERIAL SAFETY DATA SHEET

800.456.4061

WWW.SUPRESSPRODUCTS.COM

-----  
SECTION 1 - Product Identification  
-----

Product Code: SED

Description: Laminated Gypsum Panel

Product Name: SUPRESS SOUND-ENGINEERED DRYWALL

MSDS Preparer: Supress Products, LLC

P.O. Box 3472

San Rafael, CA 94912

For additional health, safety or regulatory information, to place an order, or request additional MSDS call 800.456.4061

-----  
Section 2 - Composition  
-----

BEFORE USING, HANDLING, OR EXPOSURE TO THESE INGREDIENTS, READ AND UNDERSTAND THE MSDS.

Common Name and Chemical Name

| Exposure Limits  | Weight %  | CAS Number |
|--|-----------|------------|
| Gypsum   | >78       | 10101-41-4 |
| OSHA:TLV 10 mg/M3, 15 mg/M3 STEL (Total) 5 mg/M3 (respirable)  |           |            |
| ACGIH:TLV 10.00 mg/M3 STEL (total dust, no asbestos)           |           |            |
| Cellulose(Paper fiber)   | <13       | 9004-34-6  |
| OSHA:TLV 10 mg/M3, 15 mg/M3 STEL (Total) 5 mg/M3 (respirable)  |           |            |
| ACGIH:TLV 10.00 mg/M3 STEL (total dust)                        |           |            |
| Starch   | <5        | 9004-34-6  |
| OSHA:TLV 10 mg/M3, 15 mg/M3 STEL (Total) 5 mg/M3 (respirable)  |           |            |
| ACGIH:TLV 10.00 mg/M3 STEL (total dust)                        |           |            |
| Quartz(1)  | <1        | 14808-60-7 |
| OSHA:TLV .1 mg/M3, 5 mg/M3 STEL (Total) .05 mg/M3 (respirable) |           |            |
| ACGIH:TLV .1 mg/M3 STEL (total dust)                           |           |            |
| Isoparaffinic solvent  | <1        | 64742-47-8 |
| Not listed   |           |            |
| 2-Ethyl Hexyl Acrylate   | <0.01     | 103-11-7   |
| Not listed   |           |            |
| Proprietary polymers   | Remainder | Not listed |
| Not listed   |           |            |

(1) Naturally occurring as part of minerals. See Section 3 Hazards Identification.

-----  
Section 3 - Hazards Identification  
-----

Appearance and Odor: A gypsum core wrapped with paper. Surface finish will vary with product, slight ammonia odor.

Quartz (crystalline silica) - The International Agency for Research on Cancer (IARC) classifies crystalline silica inhaled in the form of quartz or cristobalite from occupational sources as carcinogenic to humans, Group 1. The National Toxicology Program (NTP) classifies respirable crystalline silica as a substance, which may be reasonably anticipated to be a carcinogen. OSHA does not regulate crystalline silica as a human carcinogen.

It is recommended that a NIOSH approved respirator, for toxic dusts, be worn whenever working with this product results in airborne dust exposure exceeding the prescribed limits.

Skin Contact: Continued and prolonged contact may result in dry skin or irritation.

Eye Contact: Direct contact may cause mechanical irritation.

Inhalation: Target Organ: respiratory system.

Signs and Symptoms of Exposure to Airborne Dust: Continued and prolonged exposure to airborne dust

concentrations in excess of the PEL/TL V may result in cough, dyspnea, wheezing, and impaired pulmonary function.

Medical Conditions Generally Aggravated by Exposure: Overexposure would generally aggravate respiratory system dysfunctions.

-----  
Section 4 - First Aid Measures  
-----

Inhalation:

Leave area to breathe fresh air. Avoid further overexposure. \

Eyes:

Flush immediately with running water for 15 minutes, lifting the upper and lower lids occasionally. Get medical attention immediately.

Ingestion:

If accidentally swallowed, dilute by drinking large quantities of water. Immediately contact poison control center or hospital emergency room for any other additional treatment directions.

Skin:

Wash area of contact thoroughly with hand cleaner followed by soap and water. If irritation, rash or other disorders develop, get medical attention immediately.

Notes to Physician:

N/A

-----  
Section 5 - Fire Fighting Measures  
-----

Auto ignition Temperature: Not available

Upper/Lower Flammable Limits: Not applicable

Up/Lower Explosive Limits, % by Vol: Not applicable

Flash Point: Not applicable

Not Combustible

. NFPA Hazard Class No: 1/0/0

. Extinguishing Media: Dry chemical, foam, water, fog or spray.

Special Fire Fighting Procedures: Wear full protective equipment and an approved pressure demand self-contained breathing apparatus (SCBA).

-----  
Section 6 - Accidental Release Measures  
-----

Steps to be taken in Case Material is Released or Spilled: Pick-up to avoid tripping hazard.

Waste Disposal Method: Not a hazardous waste. Dispose of in accordance with applicable federal, state, and local regulations.

Precautions to be taken in Handling and Storing: Keep dry to preserve usefulness.

-----  
Section 7 - Handling and Storage  
-----

Handling and Storage Precautions:

Handle in accordance with good industrial hygiene and safety practices. These practices include avoiding unnecessary exposure and removal of the material from eyes, skin and clothing. Wash thoroughly after handling. Always use appropriate Personal Protective Equipment (PPE).

INGESTION: Do not intentionally ingest material.

-----  
Section 8 - Exposure Controls/Personal Protection  
-----

Work/Hygiene Practices: The score and snap method of cutting is recommended. Sawing, drilling or machining will produce dust.

Ventilation: Provide ventilation to maintain a dust level below the PEL/TL V.

Respiratory Protection: A NIOSH approved respirator for toxic dusts is recommended if the PEL/TL V is exceeded.

-----  
Section 9 - Physical and Chemical Properties  
-----

Odor: Slight to no odor

Appearance: Paper with gray to off-white core

Physical State: Solid

pH: ~7

Vapor Pressure: N/A

Vapor Density: N/A

Boiling Point: N/A  
Melting Point: 1450 degrees C-decomposes  
Freezing Point: N/A  
Solubility in Water: 0.26/100g  
Specific Gravity: ~2.5  
% Volatile Weight: N/A

-----  
Section 10 - Reactivity/Stability  
-----

Stability:

Stable

Incompatible Products:

Avoid contact with strong oxidizing agents.

Conditions to Avoid Polymerization:

Not Applicable

When heated to decomposition, oxides of sulfur and carbon will be released.

-----  
Section 11 - Toxicological Information  
-----

|             |             |   |
|-------------|-------------|---|
| Eyes        | SEE SECTION | 3 |
| Ingestion:  | "           | " |
| Inhalation: | "           | " |
| Skin:       | "           | " |
| Subchronic: | "           | " |
| Chronic:    | "           | " |

-----  
Section 12 - Ecological Information  
-----

Ecotoxicological Data: N/A

Chemical Fate: N/A

-----  
Section 13 - Disposal Considerations  
-----

RCRA Class: N/A

Disposal Method:

Not regulated by RCRA. Dispose of in compliance with state and local regulations.

EPA Reportable Quantities: N/A

-----  
Section 14 - Transportation Data  
-----

DOT Shipping Name: NOT REGULATED

DOT Hazard Class: NOT APPLICABLE

DOT Label:

UN /NA Number: N/A

Packing Group:

Special provisions:

Packaging

-----  
Exceptions:

Non-Bulk:

Bulk:

Quantity Limitations

-----  
Passenger Aircraft or Railcar:

Cargo Aircraft:

Vessel Stowage Requirements

-----  
Vessel Stowage:

Other Stowage:

Transportation Notes: N/A

-----  
Section 15 - Regulatory Information  
-----

15.1 U.S. Federal Regulations

Canadian Regulatory Information - This product is not classified as hazardous under WHMIS.  
European Union (EU) Regulatory Information -  
European Union Risk Phrases - none required  
European Union Safety Phrases - none required

TSCA Section 8(b) Inventory

All reportable chemical substances are listed on the TSCA Inventory.  
We rely on certifications of compliance from our suppliers.

-----  
Section 16 - Other Information  
-----

User's Responsibility

The OSHA Hazard Communication Standard 29CFR 1910.1200 and the Workplace Hazardous Materials Information System (WHMIS) require that the information contained on these sheets be made available to your workers. Trained, educated workers are your companies greatest safety asset.

Disclaimer

SELLER MAKES NO WARRANTY, EXPRESS OR IMPLIED, CONCERNING THE PRODUCT OR THE MERCHANTABILITY OR FITNESS THEREOF FOR ANY PURPOSE, except that the product shall conform to contracted specifications, and that the product does not infringe any valid United States or Canadian patent. All claims shall be limited to purchase price only. Seller is liable in no event for incidental or consequential damages, whether Buyer's claim is based on contract, breach of warranty, negligence or otherwise. Seller certifies only that the information in this sheet is, to the limits of their knowledge, accurate. Seller relies to some extent on supplier data.